

# Osprey® SSR-42R

4:1 3G SDI/DVB-ASI Reclocking Switcher

## Professional 4:1 Reclocking Switcher for 3G/HD/SD SDI and DVB-ASI

This Osprey 4 to 1 Switcher with Automatic Input Detection will accept four inputs up to 3G SDI as well as DVB-ASI. The selected channel will be passed directly to two reclocked parallel outputs. Channel selection by push buttons on the unit or with the supplied IR remote control.



### LED indicators

- Power
- Signal Lock
- Channel Select

### Video Connectors

BNC x 6

### Dimensions

4" L x 1.2" H x 6.3" W (100mm L x 30mm H x 150mm W)

### Power Connector

Locking Mini B USB

### Power

+5 VDC @ ~2.5W  
May be powered by USB charger, PC or portable battery pack (not included)

### Warranty

1 year limited hardware warranty

### In the Box

- 4:1 Switcher
- Remote Control
- Locking USB cable
- USB Power Supply

### Standards Compliance

SMPTE 259M, SMPTE 292, SMPTE 344M, SMPTE 424M  
DVB-ASI

### Video Inputs

4x 3G/HD/SD SDI and DVB-ASI with embedded Audio

### Video Outputs

2x Parallel 3G/HD/SD SDI and DVB-ASI with embedded Audio

### Reclocking

YES

### Cable Equalization (Belden 1694A)

150m at 3G, 200m at HD, 400m at SD

20150902

© 2015 Osprey by Variosystems, LLC. Osprey® & SimulStream® are registered trademarks of Variosystems AG Company. All other trademarks are the property of their respective owners. Product specifications and availability may change without notice.